



天鵝牌空氣壓縮機

AIR COOLED PISTON
COMPRESSORS

 **SWAN**

50年來，

一步一腳印，伴隨著您的成長！

SWAN has been a recognized leader in the manufacturing and marketing of air compressors for half a century, serving many of the industrial users in all corners of the globe



經熱處理及精密研磨的進排氣閥組，注意每環節確保效率與壽命。

Highly efficient and durable valve assemblies are provided through the use of special material treatments and high precision grinding processes.



以大型自動加工中心機進行精密加工，一次夾持完成各加工面，確保精度的一致性。

High quality and consistent components are maintained through the use of Numerically Controlled Machine Centers which typically are capable of completing a finished surface in a single pass.




以CAD、CAM進行分析、模擬、設計、製造、品質的發展從設計開始。

Product quality guaranteed through the application of modern technology such as CAD/CAM that is used in all functions from product development, modeling and design, right through to the manufacturing process.



鋼珠噴砂處理，自動粉體塗裝；注重環保並確保外觀晶亮耐久。

All metal surfaces on compressor units are prepared by initially shot blasting, followed by the application of powder coating to ensure you of a bright, durable and environmentally friendly surface protection.



SVP-215.220

型式 Model		S系列氣冷移動式 S Series, Air Cooled Portable Type										
		SP-114	SVP-212	SVU-201 SVP-201	SVU-202 SVP-202	SVU-203 SVP-203	SVU-205 SVP-205	SWU-307 SWP-307	SWU-310 SWP-310	SWU-415 SWP-415	SVU-215 SVP-215	SVU-220 SVP-220
馬達 Motor	KW	0.2	0.4	0.75	1.5	2.2	3.7	5.5	7.5	11	11	15
	HP	1/4	1/2	1	2	3	5	7.5	10	15	15	20
使用壓力 Working Pressure kg/cm ² /lb/in ²		8/115									7/100	
空壓機轉速 Compressor Speed(r.p.m)		675	700	1020	880	650	620	850	850	850	550	710
實際排氣量 F.A.D		l/min	36	70	140	225	355	545	872	1151	1480	2000
氣筒容量 Tank Capacity		liter	36	58	85	85	106	155	240	300	300	400
機體實體尺寸 Compressor Blocks Physical Dimensions		LxMxH(mm)	160x200x250	335x265x265	380x280x340	410x290x350	540x400x450	560x400x450	650x460x550	700x460x560	700x520x550	910x760x860
		重量(kg)	6.2	14.6	21	25	51	70	93	95	118	265
整台實體尺寸 Compressor units Physical Dimensions		LxMxH(mm)	775x290x605	940x330x700	1000x440x780	1000x440x780	1350x450x840	1400x520x980	1470x650x1150	1835x650x1200	1835x650x1200	1650x750x1480
		重量(kg)	26	52	58	62	110	168	230	250	275	560

※ 公司不斷研究改進，規格如有變更，恕不另行通知。

Keep on searching for excellence, we reserve the right to alter specifications without prior notice.

氣冷移動式

Air Cooled Portable Type



SWU-415



SWP-310



HVU-215



SVP-205



HWP-310

壓縮機機體

COMPRESSOR PUMP ONLY



SW-310



HV-205

機型選擇

- 確認需要風量並選擇至少有30% 餘裕之機型。
- 請考慮將來自動化設備增加，壓縮空氣使用量增多的情況，並預作規劃。
- 機型選擇正確與否影響購置成本及電費。

MODEL SELECTION

- Define the predicted air volume required, plus 30% to allow for an appropriate duty cycle.
- Consider any predictable future increase in air volume demand as a result of such things as increased automation equipment.
- The correct selection will minimize capital and power consumption costs.

型式選擇

- U型：用自動釋荷閥控制空壓機的空車、重車；適用於較大馬力機型及連續運轉型。
- P型：用壓力開關控制空壓機的停車及再啟動；適用於較小馬力機型及間斷使用型。
- 型式選擇正確與否影響空壓機使用壽命及電費。

CONTROL SYSTEM SELECTION

- **AUTOMATIC UNLOADER SYSTEM "U" TYPE**
The automatic unloading system allows for the control of loaded and unloaded compressor states through a range of pre-set pressure values. This system is recommended where the duty cycle exceeds 50%, and for all larger compressors units.
- **PRESSURE SWITCH SYSTEM. "P" TYPE**
The automatic pressure switch will stop and start the compressor according to air demand. It is normally recommended for intermittent operation and smaller compressor units.
- **The correct selection will extend compressor service life and reduce power consumption.**

規格 Size		型式 Model	H系列氣冷移動式 H Series, Air Cooled Portable Type							
			HVU-202 HVP-202	HVU-203 HVP-203	HVU-205 HVP-205	HWU-307 HWP-307	HWU-310 HWP-310	HVU-215 HVP-215	HVU-230 HVP-230	
馬達 Motor	KW		1.5	2.2	3.7	5.5	7.5	11	22	
	HP		2	3	5	7.5	10	15	30	
使用壓力 Working Pressure kg/cm ² /11b/in ²			16/230				12/175			
空壓機轉速 Compressor Speed(r.p.m)			550	960	900	850	850	710	800	
實際排氣量 F.A.D		l/min	154	270	406	606	786	1064	2464	
氣筒容量 Tank Capacity		liter	237	237	237	237	237	300	300	
機體實體尺寸 Compressor Blocks Physical Dimensions		LxMxH(mm)	500x330x400	500x330x400	560x380x460	620x480x530	650x480x540	930x650x690	990x920x870	
		重量(kg)	47	47	67	93	95	280	500	
整台實體尺寸 Compressor units Physical Dimensions		LxMxH(mm)	1450x550x1100	1470x550x1100	1470x550x1100	1470x640x1150	1470x640x1150	2230x800x1400	2600x900x1250	
		重量(kg)	205	205	225	260	262	515	765	

※ 規格外之壓力、排氣量、傳動方式，歡迎訂購，詳細資料請隨時與本公司洽商。
Different pressure, discharge air volume and driven type are also available on enquiry.



東正鐵工廠 股份有限公司

TONG CHENG IRON WORKS CO.,LTD

公 司：台中市東區信義街116號

Head Office：116 Shing Yee St., Taichung, Taiwan

TEL:886-4-2261-2135 FAX:886-4-2261-5465

廠 址：台中市南區大慶街二段16號

F a c t o r y：16 Ta Chin St. Sec.2, Taichung, Taiwan

TEL:886-4-2261-2135 FAX:886-4-2262-8246

w e b s i t e：w w w . s w a n a i r . c o m . t w



台北營業所：台北縣五股工業區五權五路43號

TEL:02-2299-1285 FAX:02-2298-2296

台中營業所：台中市南區大慶街二段16號

TEL:04-2261-2135 FAX:04-2261-5465

台南營業所：台南縣永康市中正南路635號

TEL:06-253-9848 FAX:06-253-9849

E-Mail:swantc@swanair.com.tw